

## Material Safety Data Sheet

### VP 10 – Oil

**Issue Date**

April 2008

**Status** ISSUED by  
Clements

**This preparation is not classified as dangerous according to Directive 1999/45/EC**

#### COMPANY DETAILS

**Company Name** Clements Medical Equipment  
**Address** 5 Cal Close  
Somersby NSW 2261  
**Emergency Tel.** 02 43 40 2484  
**Tel/Fax** Tel: (02) 4340 2484 Fax: (02) 4340 5121

#### IDENTIFICATION

**Product Code** SUC80101 / SUC 80102 / SUC80103  
**Product Name** VP 10  
**Proper Shipping Name** None Allocated  
**Other Names** None Listed  
**UN Number** None Allocated  
**DG Class** None Allocated  
**Packing Group** None Allocated  
**Hazchem Code** None Allocated  
**Poisons Schedule** Not Scheduled  
**Product Use** Air compressor oil.

#### Physical Data

**Appearance** Pale straw to clear amber oil.  
**Boiling Point** Not available.  
**Vapour Pressure** Not available.  
**Specific Gravity** 0.883  
**Flash Point** 210°C  
**Flamm. Limit**  
**LEL** Not available.  
**Solubility in Water** Insoluble

#### Other Properties

<b>Corrosiveness</b>	Not corrosive to aluminium.
<b>Autoignition Temp.</b>	>400°C
<b>Stability</b>	Stable under normal conditions of storage and handling.
<b>Haz.</b>	
<b>Polymerization</b>	Will not occur.
<b>Materials to Avoid</b>	Strong oxidising agents.

---

## Ingredients

---

Ingredients Name	CAS	Proportion
Ingredients determined not to be hazardous	Not required	100 %

---

## HEALTH HAZARD INFORMATION

---

### Health Effects

<b>Acute - Swallowed</b>	May cause irritation to the mouth, oesophagus and stomach. Vomiting may lead to aspiration into the lungs with a possibility of a type of pneumonia.
<b>Acute - Eye</b>	May cause slight to moderate eye irritation, resulting in redness and stinging. Not anticipated to cause permanent eye injury.
<b>Acute - Skin</b>	May dry and defat the skin, resulting in skin irritation and possible dermatitis.
<b>Acute - Inhaled</b>	May cause irritation to the mucous membrane and upper airways, especially if the material is heated or mists are generated.
<b>Chronic</b>	Prolonged or repeated contact with this material may result in skin irritation leading to dermatitis.

---

### First Aid

<b>Swallowed</b>	DO NOT induce vomiting. Immediately wash out mouth with water, and then give water to drink. Seek medical attention.
<b>Eye</b>	If contact with the eye(s) occur, wash with copious amounts of water for approximately 15 minutes holding eyelids(s) open. Take care not to rinse contaminated water into the non-affected eye. If irritation develops and persists seek medical attention.
<b>Skin</b>	Remove all contaminated clothing. Wash gently and thoroughly with water and non-abrasive soap. Ensure contaminated clothing is washed before re-use or discard. If irritation develops and persists seek medical attention.
<b>Inhaled</b>	Remove the source of contamination or move the victim to fresh air. Ensure airways are clear and have qualified person give oxygen through a facemask if breathing is difficult. If irritation develops and persists seek medical attention.
<b>First Aid Facilities</b>	Eye wash and normal washroom facilities.

---

### Advice to Doctor

<b>Advice to Doctor</b>	Treat symptomatically.
-------------------------	------------------------

---

## Other Health Hazard Information

---

---

### PRECAUTIONS FOR USE

---

<b>Exposure Limits</b>	No value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC). However, Exposure Standards for oil mist are listed below. SUBSTANCE TWA STEL ppm mg/m <sup>3</sup> ppm mg/m <sup>3</sup> Oil mist, mineral - 5 - 10 Exposure Standard means the average concentration of a particular substance in the worker's breathing zone, exposure to which, according to current knowledge, should not cause adverse health effects nor cause undue discomfort to nearly all workers. It can be of three forms; time-weighted average (TWA), peak limitation, or short-term exposure limit (STEL).
<b>Eng. Controls</b>	Natural ventilation should be adequate under normal conditions of use. Where vapours or mists are generated and exposure standards are exceeded, the use of respiratory protection, or a local exhaust ventilation system is recommended.

---

### Personal Protection

---

<b>Respirator Type (AS 1716)</b>	Avoid breathing of vapours, mists or spray. Select and use respirators in accordance with AS/NZS 1715/1716. When mists or vapours exceed the exposure standards then the use of the following is recommended: Approved respirator with organic vapour and dust/mist (Type P1) filters. Filter capacity and respirator type depends on exposure levels.
<b>Eye Protection</b>	Safety goggles or face shield as appropriate.
<b>Glove Type</b>	PVC or nitrile rubber gloves recommended.
<b>Clothing</b>	PVC or nitrile aprons where clothing is to be contaminated.

---

### Flammability

---

<b>Fire Hazards</b>	Classified as a Class C2 (Combustible liquid). Remove all sources of heat and ignition.
---------------------	---

---

## SAFE HANDLING INFORMATION

---

---

### Storage and Transport

---

<b>Storage Precautions</b>	Classified as a class C2 combustible liquid for storage and handling purposes. Store in a cool, dry, well-ventilated area, out of direct sunlight. Avoid sparks, flames, and other ignition sources. Store away from incompatible materials such as materials that support combustion
----------------------------	---

<b>Transport</b>	(oxidising materials). Reference should be made to Australian Standard AS1940- The storage and handling of flammable and combustible liquids. Not classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.
<b>Handling</b>	Repeated or prolonged contact with lubricants and industrial oils should be avoided in order to lessen the possibility of skin disorders. It is essential that all who come into contact with lubricants and industrial oils maintain high standards of personal hygiene ie. Washing hands prior to eating, drinking or going to the toilet. Build-up of oil mists in the working atmosphere must be prevented.
<b>Proper Shipping Name</b>	None Allocated

## Spills and Disposal

<b>Spills &amp; Leaks</b>	SMALL - 20 LITRES OR LESS Soak up on Diatomaceous Earth or similar inert oil absorbent. Arrange for disposal through an approved facility. LARGE - GREATER THAN 20 LITRES Remove all sources of ignition. Increase ventilation. Evacuate all unnecessary personnel. Wear full protective equipment and clothing to minimise exposure. If possible contain the spill. Place inert absorbent material such as vermiculite, sand or dirt onto spillage. Use clean non-sparking tools to collect the material and place into a suitable labelled container. Do not dilute material but contain. If large quantities of this material enter the waterways contact the Environmental Protection Authority, or your local Waste Management Authority.
<b>Disposal</b>	Dispose of waste according to federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

## Fire/Explosion Hazard

<b>Fire/Explos. Hazard</b>	Classified as a Class C2 (COMBUSTIBLE LIQUID).
<b>Hazardous Decomposition or Byproducts</b>	Oxides of carbon.
<b>Fire Fighting Procedures</b>	Self-Contained Breathing Apparatus (S.C.B.A) and full protective clothing should be worn.
<b>Extinguishing Media</b>	Carbon dioxide, dry chemical or foam.
<b>Hazchem Code</b>	None Allocated

## OTHER INFORMATION

<b>Toxicology Environment Protection</b>	No toxicity data is available for this product. Prevent this material from entering the environment. This substance presents environmental risks common to oil spills.
--	--

## CONTACT POINT

<b>Contact</b>	For information concerning details on this Safety Data Sheet contact :- Clements Medical Equipment 5 Cal Close Somersby NSW 2261 Phone: 02 4340 2484
----------------	--

Fax: 02 4340 5121

**IMPORTANT DISCLAIMER**

All reasonable care has been taken to ensure that the information and advice contained herein are accurate at the time of printing. However, Clements accepts no tortious or contractual liability for any loss or damages suffered as a consequence of reliance on the information and advice contained herein.

---

**End of MSDS**

---